

Venom Replacement Screen

Specifications & Dimensions

Fits shaker machines: Brandt® Venom


Quantity per shaker: 3 - 4

Type of Screen: Frame/Pre-tensioned

Gasket: Yes

Weight: 37 pounds (16.78 kg)

Approx. Dimensions: 49" x 25" x 1"



Mesh & API Information

CWC Mesh Type	CWC Mesh Size	API RP 13C Designation	D100 Cut Points (Microns)	API Micron Range for Screen Designation	Continental Wire Cloth Item #
CRX Oblong	60	API 50	321	275-327.50	FR-CRXVENOM060
CRX Oblong	84	API 60	233	231-275	FR-CRXVENOM084
CRX Oblong	110	API 70	207	196-231	FR-CRXVENOM110
CRX Oblong	140	API 80	172	165-196	FR-CRXVENOM140
CRX Oblong	175	API 100	139	137.50-165	FR-CRXVENOM175
CRX Oblong	210	API 120	131	116.50-137.50	FR-CRXVENOM210
CRX Oblong	250	API 140	101	98-116.50	FR-CRXVENOM250
CRX Oblong	270	API 170	86	82.5-98	FR-CRXVENOM270*
CRX Oblong	325	API 200	73	69-82.5	FR-CRXVENOM325
CRX Oblong	400	API 230	67	58-69	FR-CRXVENOM400
UF Square	24	API 20	861	780-925	FR-UFVENOM024
UF Square	38	API 35	521	462.5-550	FR-UFVENOM038
UF Square	50	API 45	373	327.5-390	FR-UFVENOM050
UF Square	70	API 60	263	231-275	FR-UFVENOM070
UF Square	84	API 70	212	196-231	FR-UFVENOM084
UF Square	110	API 80	185	165-196	FR-UFVENOM110
UF Square	140	API 100	150	137.5-165	FR-UFVENOM140
UF Square	175	API 120	125	116.5-137.5	FR-UFVENOM175
UF Square	210	API 140	106	98-116.5	FR-UFVENOM210
UF Square	230	API 170	90	82.5-98	FR-UFVENOM230
UF Square	250	API 200	76	69-82.5	FR-UFVENOM250*
UF Square	325	API 230	66	58-69	FR-UFVENOM325
UF Square	350	API 270	54	49-58	FR-UFVENOM350
UF Square	400	API 325	47	41.5-49	FR-UFVENOM400

The Continental Wire Cloth Difference

Continental Wire Cloth replacement shaker screens offer the oil industry a superior product—longevity, increased flow, durability and competitive prices.

make **The Black Screen™**
your last screen

Continental Wire Cloth does not manufacture screens for NOV Brandt®. CWC manufactures replacement screens that give our customer an alternative option for their solids control needs. Standard mesh sizes are listed above for other available sizes please contact our sales department.

* Results from in house testing.